

Amendment filed May 6, 2005

Reply to Office Action of February 7, 2005

IN THE CLAIMS

11-13 (Canceled).

14. (Currently Amended) A gas turbine according to claim 1, in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying refrigerant for cooling to said moving blades and a recovery flow path for recovering heated refrigerant, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs; and

wherein said recovery flow path is arranged on a more radially outer side than said supply flow path, and

Amendment filed May 6, 2005

Reply to Office Action of February 7, 2005

wherein said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.

15. (Canceled)

16. (Currently Amended) A gas turbine ~~according to claim 1,~~ in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying refrigerant for cooling to said moving blades and a recovery flow path for recovering heated refrigerant, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs; and

Amendment filed May 6, 2005

Reply to Office Action of February 7, 2005

wherein said recovery flow path is arranged on a more radially outer side than said supply flow path, and

wherein the fluid introduced into said gap portions is exhausted therefrom into a gas flow path of said gas turbine.

17. (New) A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

a supply flow path for supplying steam for cooling to said moving blades and a recovery flow path for recovering heated steam, each of said supply and recovery flow paths being provided in said rotor shaft; and

a flow path for introducing fluid into said gap portions, provided in said discs; and

wherein said recovery flow path is arranged on a more radially outer side than said supply flow path, and

Amendment filed May 6, 2005

Reply to Office Action of February 7, 2005

    said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.

18. (New) A gas turbine in which a rotor shaft comprises a plurality of discs each having a plurality of moving blades arranged annularly on a peripheral portion, and spacers arranged between said discs, said respective discs and spacers being arranged in an axial direction in turn, comprising:

    gap portions formed between rotor axis side regions of said discs facing said spacers and adjacent spacers;

    a supply flow path for supplying steam for cooling to said moving blades and a recovery flow path for recovering heated steam, each of said supply and recovery flow paths being provided in said rotor shaft; and

    a flow path for introducing fluid into said gap portions, provided in said discs; and

    wherein said flow path for introducing fluid into said gap portion is constructed so as to be supplied with air extracted from a compressor, and arranged on a more radially inner side than said supply flow path,

said recovery flow path is arranged on a more radially outer side than said supply flow path; and

    said flow path for introducing fluid into said gap portion is arranged on a more radially inner side than said supply flow path.